The MGS Group






MEASURING MACHINES

Our caterpillar-type measuring machines are designed to provide accurate length measurement with no slippage and include the following features:

- Two zero stretch endless timing belts for traction.
- Product contact length is approximately 8 inches.
- Adjustable offset inlet and outlet guide rollers designed into the unit.
- Caterpillar tracks open pneumatically for string up.
- Quadrature encoder.
- + / .10% accuracy.
- Lexan guard.

MODEL	STANDARD DIAMETER RANGE
CAT 150	.020 to 1.625 inches
CAT 300	.020 to 3 inches
CAT 500	.500 to 5 inches

- Adjustable height stand.
- 6 digit bi-directional counter.
- Extra encoders.
- Steel guard.





PRODUCT HANDLING AND TWISTING EQUIPMENT

Payoffs and Takeups

Moveable Arm 30" to 168" - Drag - Powered - Fixed - Traversing Roll Thru 72" to 144" – Standard – Traversing Frame – Traversing Reel Cantilever 6" to 40" – Single – Dual – Multiple Spindle

Cone Pintle 12" to 50" - Single - Dual

Back Twist - Multiple

Flyer – Single – Multi-Wire



Moveable Arm 40" to 120" Cantilever Shaft 12" to 30"

Fully Automatic Takeup Systems

Reels 6" to 24" Coils 6" to 20" flange ReelBOT Depalletizing/Palletizing Labeling – Sequential Printing

Dancers

Float Arm - Multi Pass - Single Pass 4" to 60" flange

Accumulators

6" to 60" Vertical – up to 1000' Horizontal – up to 4500' Ribbon - Strip

Capstans

Caterpillar 10" to 120" Belt Wrap 6" to 48" Dual Drum 12" to 48" - Wet - Dry Underbeam

Bunchers / Twinners

Single Twist **Double Twist Group Twinners** Triple Twist

Measuring Machines

Caterpillar

Rewinders **Air Wipes**



Swage Tools



Electric Brazers



























The MGS Group

www.themgsgroup.com | sales@themgsgroup.com | 315-337-3350